

Uncoated papers

Toner

Water

(eco) Solvent

UV Curable

Latex

IJM009 Draft Paper - PEFC

75 g/m²

Product Description

An uncoated paper for line drawings and check prints with simple fills.

Physical Properties

Weight (g/m ²)	75	ISO 536	Opacity (%)	93.0	ISO 2471
CIE whiteness (%)	164.0		Roughness Bendtsen (ml/min)	220.0	ISO 8791-2
L*: a*: b*	92.2; 2.8; -9.1				

Applications/features

Available Widths (mm)

2"core (mm)	297	420	594	610	841	914	1067
Length (m)	120	120	120	50	50/91/120/150	50/91/120/150	50

Storage Conditions

Temperature between 20 ± 3°C and 50 ± 5% RH.

Lamination Compatibility

Cold	Warm	Hot	Cold: pressure sensitive
yes	no	no	Warm: heat activated: 85°C - 95°C
			Hot: heat activated: 105°C -130°C

Outdoor Use

This uncoated paper is developed for indoor use.

Colour Profiles

Canon develops high-quality colour profiles for media / ink / printer / RIP combinations. Check availability of profiles for your printer on mediaguide.oca.com

Environmental Certification



Processing Guidelines

Printing guidelines

It is recommended to handle the media with cotton gloves. Insert media with care in the printers. Incorrect loading can cause skewing or creasing. Allow material to adapt to room conditions for 24 hours before printing. It is recommended to

calibrate the printer before printing and to make a test print. Print results will vary for different printers.

Ink/toner restrictions and printer settings have to be set for specific printers to obtain the best results. Canon colour profiles include recommended ink restrictions and printer settings for Canon supported printers.

Standard disclaimer:

All specifications subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition 0615
© Canon Europa N.V., 2017

The Canon logo, consisting of the word "Canon" in a bold, red, sans-serif font.